



TROPICAL THUNDER RA2 WITH CEILING ELEMENT PVC

FUNCTION DESCRIPTION

Programme 1: Tropical Rain

After the start of the programme by a button the light in the shower changes from white to a red-green colour change and a soft, warm Drizzle Rain patters onto the guest in the shower. You hear birds tweeting. In the following, a warm String Rain starts. A fruity, lively aroma fills the air. Now a cold Drizzle Rain cools the temperature down. Then the cold Drizzle stops and the programme finishes with a warm Drizzle and the aromatised String Rain. After the end of the programme the illumination changes from the red-green colour change back to white, the warm Drizzle and the aromatised String Rain are switching off.

Programme 2: Caribbean Rain

The programme starts with a warm Drizzle Rain and red light. In a distance you hear the sound of waves and sea. After an adjustable time the light changes to green and a cold, refreshing Fog with very fine droplets refreshes the user. A minty, cooling aroma fills the air. In the following the warm Drizzle stops and the cold Fog continues. Now a warm Tropical Rain with blue light starts and then goes over into a warm Drizzle. You hear a thunderstorm coming and you see flashlights. In the next step a cold Drizzle Rain replaces the cold Fog. The scenario lapses with a warm Drizzle Rain and red light. After the end of the programme the illumination changes back to white, the Drizzle Rain and the sound are switching off.

SCOPE OF DELIVERY OF A COMPLETE PACKAGE

CONTROL PANEL



Control panel incl. listed parts, pre-tubed, pre-wired and pre-mounted on PP board grey - Part no. 19290:

- 2 x Supply with pre-filter and ball valve MS 3/4" female thread
- Thermomixer JRG 3/4" with non-return valves
- 6 x Outlet with solenoid valve 1/2" and screwing 1/2"
- Emptying for the tube to the aromatised rain nozzle
- 2 x Fragrance pump with fragrance reservoir and empty switch
- 2 x Dosing valve for the injection of aroma into the water tube
- 2 x Microprocessor controller EDS1 in housing

TECHNICAL DATA

Electrical supply	230 V-AC, 50 Hz
Power supply	150 W
Water supply	2 x 3/4" female thread
Dimensions (W/H/D)	1000 x 750 x 200 mm
Weight	app. 20 kg

PUSH BUTTON

Details see page 72



- 1 x Push-button plate 2-fold Alu-Dibond - Part no. 19012
- 1 x Bonnet 2-fold - Part no. 21034-1
- 1 x Name plate "Tropical Rain" - Part no. 17528
- 1 x Name plate "Caribbean Rain" - Part No. 23447

CEILING ELEMENT INCL. ILLUMINATION

Details see page 76



1 x Ceiling element PVC white Ø 800 x 19 mm with 3 LED Spots RGB Ø 48 incl. RGB controller SAU and 7 m cable with 11 connections for 11 nozzles - Part no. 21772-1

NOZZLES

Details see page 74

- 1 x Rain Nozzle 1/2" - Part no. 13528
- 1 x Cover Screen for Rain Nozzle - Part no. 13879
- 2 x Fog Nozzle 1/2" - Part no. 13526
- 2 x Cover Screen for Fog Nozzle - Part no. 13877
- 5 x Drizzle Nozzle 1/2" - Part no. 13527
- 5 x Cover Screen for Drizzle Nozzle - Part no. 13878
- 3 x String Nozzle 1/2" - Part no. 16593
- 3 x Cover Screen for Fog Nozzle - Part no. 13879

SOUND

Details see page 80



- 1 x Sound module MP3 - Part no. 18824-1
- 1 x Speaker - Part no. 14366-4

TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Water connection cold 3/4"
- Water connection warm 3/4"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 60 l/min
- Drain in the plants room
- Tubing to the nozzles
- 2 x Non-return according to DIN EN 1717

ACCESSORIES / OPTIONS

- Optionally you can use Corian® or backlit ceiling element instead of PVC
- Fragrance