



SHOWER TUNNEL WITH CEILING ELEMENTS PVC WITH 3 ZONES

FUNCTION DESCRIPTION

In standby mode all zones are illuminated white. Once the tunnel has been activated, the white light switches-off and only the currently activated zone is illuminated. The overlap time between the single zones is three seconds. The shower walk starts with a warm, aromatised Drizzle Rain and red lights. Birds tweeting. At the second station, a cold String Rain patters on the guest in the shower, the illumination changes to blue. You hear crashing of waves. In the third zone a warm Tropical Rain starts, flashlights fill the room and you hear the roll of thunder. In the following the second station will surprisingly be activated again with a cold Fog. A blue-green colour change fills the room and you hear the crashing of waves again. The programme lapses in the third station with a warm Drizzle Rain. The lights shines yellow and you hear a final roll of thunder. Afterwards the tunnel is ready for a restart.

SCOPE OF DELIVERY OF A COMPLETE PACKAGE

CONTROL PANEL



Control panel incl. listed parts, pre-tubed, pre-wired and pre-mounted on PP board grey - Part no. 19374-1:

- 2 x Supply with pre-filter and ball valve MS 1" female thread
- Thermomixer JRG 3/4" with non-return valves
- 3 x Outlet with solenoid valve warm 3/4" and screwing 3/4"
- 2 x Outlet with solenoid valve cold 3/4" and screwing 3/4"
- 1 x Fragrance pump with fragrance reservoir and empty switch
- 1 x Dosing valve for the injection of aroma into the water tube
- 1 x Microprocessor controller EDS1 in housing

TECHNICAL DATA

Electrical supply	230 V-AC, 50 Hz
Power supply	150 W
Water supply	2 x 1" female thread
Dimensions (W/H/D)	1000 x 750 x 200 mm
Weight	app. 20 kg

PUSH BUTTON

Details see page 72



- 1 x Push-button plate 1-fold Alu-Dibond - Part no. 19011
- 1 x Bonnet 1-fold - Part no. 21030-1
- 1 x Name plate "Start" - Part no. 17219

CEILING ELEMENT INCL. ILLUMINATION

Details see page 76



Example photo

2 x Ceiling element PVC white 700 x 700 mm, 2 cm with 3 LED Spots RGB MS chromed incl. RGB controller SAU and 7 m cable with 3 connections for 3 nozzles - Part no. 24948

1 x Ceiling element PVC white 700 x 700 mm, 2 cm with 3 LED Spots RGB MS chromed incl. RGB controller SAU and 7 m cable with 6 connections for 6 nozzles - Part no. 24946

NOZZLES

Details see page 74

- 3 x Rain Nozzle 1/2" - Part no. 13528
- 3 x Cover Screen for Rain Nozzle - Part no. 13879
- 3 x Fog Nozzle 1/2" - Part no. 13526
- 3 x Cover Screen for Fog Nozzle - Part no. 13877
- 6 x Drizzle Nozzle 1/2" - Part no. 13527
- 6 x Cover Screen for Drizzle Nozzle - Part no. 13878
- 3 x String Nozzle 1/2" - Part no. 16593
- 3 x Cover Screen for Fog Nozzle - Part no. 13879

SOUND

Details see page 80



- 1 x Sound module MP3 - Part no. 18824-1
- 1 x Speaker - Part no. 14366-4
- 2 x Relais board WDT-NT-34 RSL-V2 - Part no. 24926

TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Water connection cold 1"
- Water connection warm 1"
- Needed pressure: 3 bar dynamic
- Water quantity: app. 60 l/min
- Drain in the plants room
- Tubing to the nozzles
- 2 x Non-return according to DIN EN 1717

ACCESSORIES / OPTIONS

- Optionally you can use Corian® or backlit ceiling element instead of PVC
- Fragrance