



# FOAMDOS V7

## FUNCTION DESCRIPTION

The FOAMDOS produces foam for Hammam massages by the three components water, air and foam agent. The foam outlet is via hand shower or on-site wall fitting. Furthermore a shower function with warm water is integrated. The dosing quantity of the foam agent, the water flow and so the consistency of the foam is adjustable individually at the controller. Operation and visualisation via 5-line LC display and three buttons. Both functions are started by a push-button.

## SCOPE OF DELIVERY

- Controller CB36 with 5-line LC display installed in housing
- Diaphragm air pump 7006 AC
- Supply with pre-filter and ball valve MS 1/2" female thread
- Non-return according to DIN EN1717
- Pressure gauge
- Flow regulator
- 2 x solenoid valve 3/8"
- Foam generator
- Peristaltic dosing pump SA
- Suction lance d 12-420 mm
- 2 x dosing valve for foam agent and air
- 3 m hose PVC 12 x 1,5 transparent for the outlet of the foam
- Push-button plate 2-fold
- Completely tubed and pre-wired on PP board grey

## TECHNICAL DATA

Electrical supply	230 V / AC 50 Hz
Power supply	150 W
Water supply	1/2 " IG
Measures BxHxT cm	50 x 50 x 25
Weight	app. 10 kg



## TO BE PROVIDED BY THE BUILDER

- Plants room for the installation of the control panel
- Power supply
- Thermo mixer/Water supply mixed water 1/2"
- Needed pressure: 2 bar dynamic
- Water quantity: app. 10 l/min
- Waste water connection for the system separator, if necessary with option emptying
- Drain in the plants room
- Foam outlet: hand shower or wall outlet with bowl

## ACCESSORIES/ OPTIONS

- Thermo mixer
- Hand Shower for the foam outlet
- Emptying

