



MODULECONCEPT

Due to the fact that there is often very limited space for the technique for steam rooms, we have developed a system, where all technical components for a steam room are pre-installed and pre-wired on a mounting plate. This mounting plate will be installed space saving on a second plate with slide rails in a technique niche. Therefore a quick and easy installation and maintenance of the complete steam room technique is ensured.

PLUG'N PLAY



FLEXIBLE PLANNING

- » Pre-installed and pre-wired technical components on mounting plates with slide rails
- » Very low space requirements for the steam room technique due to a compact design
- » Flexible configuration of the necessary components – easy and quick installation
- » Especially synchronised on multifunctional SPA EMOTION steam showers with heat storage ceramic in cooperation with LUX Elements und Sommerhuber Keramik

We consult you with pleasure about detailed configuration possibilities



MODULECONCEPT

EXEMPLARY SCOPE OF DELIVERY
as a complete package for one steam room with
a room volume of max. 5 m³ with one bench

STEAM GENERATOR



- 1 x Steam generator - Standard Line - SLE05 - Part no. 29459
- 3 m Steam hose DN25 - Part no. 17125
- 1 m Drain hose 1¼" - Part no. 17000

FRAGRANCE PUMP



- 1 x DUFTDOS-0-230V Compact - Part no. 17630



- 1 x Dosing set consisting of:
Dosing valve VA ¾" 4 x 1 and 3 m dosing hose
PTFE 4 x 1 - Part no. 12596

CONTROL SYSTEM



- Controller in metal control box 380 x 380 x 210 mm (W/H/D) with main switch
- Touch Screen 4,3", 64000 colours, full-graphic
- Box for in-wall mounting of the Touch-Screen
- 2 x PT1000 temperature sensors with 5 m connection cable

Controls:

- Steam generator (on/off, temperature controlled)
- Exhaust fan (230 V, temperature controlled)
- Fragrance pump (230 V, pulse-pause time)
- Illumination circuit Spots (230 V, on/off)
- Illumination circuit Linelights (230 V, on/off)
- Bench heating (230 V, on/off, temperature controlled)
- Measuring of the room temperature (PT1000)
- Measuring of the bench temperature (PT1000)
- Connection accumulative fault message of the steam generator

Operation via Touch Screen 4,3", 64000 colours, full-graphic with box for in-wall mounting


ILLUMINATION



- 2 x LED Spots warm white IP67 - Part no. 21640 (quantity according to detailed cabinet size)
- 2 x Mounting sleeve for LED (quantity according to detailed cabinet size, characteristic according to ceiling construction)
- 1 x Extension cable (quantity and lengths according to detailed cabinet size)



- 1 x Dimmable transformer for LED Spots warm white - Part no. 27404



Linelights according to lengths and shape of the bench on demand

MOUNTING BOARDS / GUIDE-RAIL



Factory-made pre-installation of above components on mounting boards with guide-rails consisting of:

- 2 x Mounting board (1 x base- / 1 x guide-rail-board) W 700 mm x H 1830 mm x D 550 mm
- 3 x Guide-rail
- Factory-made pre-installation and -wiring